

DEINES MANUFACTURING CORPORATION
1800 HT SERIES COMMERCIAL TRACTOR SPECIFICATIONS

ENGINE	Kohler Command 18HP Overhead Valve Design Hydraulic Valve Lifters Electronic Ignition Dual Element Air Cleaner Closed Breather System Stellite Exhaust Valves, w/Seat Inserts and Rotators Full Pressure Lubrication In-line Fuel Filter Easy Access Valve Cover Oil Fill Oil Level Dipstick Oil Filter Dual Oil Drain Oil Sentry Variable-Speed Governor Fuel Shutdown Solenoid Self-relieving Smart-Choke Carburetor Pulse fuel pump 12-Volt Shift Starter
FUEL TANK	5 Gallon Capacity, plastic with reinforced filler neck
FUEL GAUGE	Float Type, by Kelch
WHEELS	10"
DRIVE TIRES	2-Ply, Pneumatic 20-10:00 x 10 Turf Saver, 18-8:50 X 10 Turf Saver, on D-1850-HT only.
DUAL TAILWHEEL	Standard on all 2000 Series Tractors
REAR TIRE SIZE	2-Ply 15-6:00 x 6 Rib, Tubeless Tires
STEERING	2 Levers, One For Each Hydrostatic Transmission
TURNING RADIUS	Zero Degrees Right and Left
SPEEDS	Infinite Variation From 0-7.5 MPH
TRANSMISSIONS	Parker/Hannifan-Model H110A2011HAAAA, 2 Each
WHEEL MOTORS	Ross MF-16 Motors, 2 Each
MAXIMUM WEIGHT	1,000 Pounds Per Drive Wheel
TRANSMISSION OIL RESERVOIR CAPACITY	3 US Gallons
PARKING BRAKE	Band & Drum Type
ENGAGING SYSTEM	Electric Clutch
DECK LIFT	Manual Deck Lift
NET WEIGHT	725 Pounds
HEIGHT	44 Inches
LENGTH	70 Inches
WIDTH	47 Inches
ATTACHMENTS	50 SLI, AND 60 SLI Decks. DST 48 Snowthrower. 50 SLI Deck Requires 18-8:50 x 10 Turf Saver Tires